



**T/25 Model Pump
New Compact Functional
"900 r.p.m. - 4 bar" (50 psi)**

Self-priming pump entirely made of 304 cast stainless steel, equipped with neoprene impeller, available with or without bypass.

Suitable for decantation of liquids such as wine, water, oil ...

Since it develops 4 atmospheres, at 900 rpms, it is suitable for high-quality filtration.



**T-25 senza by pass
T-25 con by pass**

T 25 SERIES



From left: T-25 SPECIAL, T-25 EXPORT, T-25 without trolley and with bypass, T-25 without trolley and without bypass



NEW MODEL T-25 with frequency drive controller with bypass. Can be supplied 1-ph or 3-ph.

Model	t/25 senza by pass	t/25 con by pass	t/25 export by pass	t/25 special by pass
Code	5900 (3-ph) 5901(1-ph)	5902 (3-ph) 5903(1-ph)	5904 (3-ph) 5905(1-ph)	5906 (3-ph) 5907(1-ph)
r.p.m.	900	900	900	900
Flowrate	2500 lt/h	2500 lt/h	2500 lt/h	2500 lt/h
Pressure	3,5 bar	3,5 bar	3,5 bar	3,5 bar
Dimensions	mm 325x210x300	mm 325x210x300	mm 500x300x670	mm 500x300x650
Weight	kg. 14,8	kg. 15	kg. 16	kg. 17
Standard Motor	Volt 400 kW 0,55	Volt 400 kW 0,55	Volt 400 kW 0,55	Volt 400 kW 0,55
	Volt 230 kW 0,4	Volt 230 kW 0,4	Volt 230 kW 0,4	Volt 230 kW 0,4

All our pumps can be supplied with special motor voltages and special fittings. Do not hesitate to contact us, we have the right pump for you!