



**T/70 Model Pump
Self-priming Pumps - Inox
"900 r.p.m. - 4 bar" (50 psi)**

Suited for decanting wine and alimentary liquids, it is particularly fit for filling demijohns and containers in general.

Suction is possible in both directions. The rubber impellers prevent the shaking of the decanted liquids.

It works at low r.p.m., the flow is steady and quite gentle and according to its principle of working this pup can be called a "rotary piston pump".



**T/70 Inverter
with remote radio-
control
Code T-70/ICDR**



**From Left to Right: Code T-70/VM-1 speed (900 rpm),
Code T-70/FL-Axial 2 speed, Code T-70/A2V**

Models and Specifications

Model	T/70 FL	T/70 A2V	T/70 VM0	T/70 VM155	T/70 ICDR
Code	5852(3-ph)5853 (1-ph)	5254 (3-ph)	5362 (3-ph) 5363 (1-ph)	5352 (3-ph) 5353 (1-ph)	5931 (3-ph) 5932 (1-ph)
r.p.m.	900	I 380 II 760	0÷900	155÷1000	32÷750
Flowrate	6300 lt/h	I° 3150 II° 6300 lt/h	0÷6300 lt/h	120÷7500 lt/h	350÷6500 lt/h
BAR max	3,5	3,5	3,5	3,5	3,5
Ø Connectors	40	40	40	40	40
Motor	3-ph 0,9 kW 1- ph 0,9 kW	3-ph 0,8-0,6 kw	3-ph 0,75 kW 1- ph 1,5 kW	3-ph 0,75 kW 1- ph 1,5 kW	3-ph 0,75 kW
kg Weight	20	37	53	45	41
mm. Dimensions	370x660 h.620	400x880 h.740	400x880 h.740	400x880 h.740	400x880 h.740

All our pumps can be supplied with special motor voltages and special fittings. Do not hesitate to contact us, we have the right pump for you!